

The VOIS+ is an integrated Voltage Detecting Systems VDIS for checking for absence of voltage in medium voltage switchgear according to IEC 62271-213:2021 (or IEC 61243-5) with integrated three-phase continuous indication.



### Properties

#### Voltage Detecting Systems for Medium Voltage (VDIS)

Integrated three-phase Voltage Detecting Systems for medium voltage switchgear according to IEC 61243-5 and IEC 62271-213

#### No battery required

Voltage indication without battery or auxiliary voltage

#### Integrated three-phase measuring point

The device has a three-phase LR measuring point for phase comparison, rotating field direction measurement, etc.

#### Favorable alternative

to plug-in voltage indicators.

#### System connector

To easily connect a three phase cable set for the sensors

## Technical Data

### Device data

Article number	2502062_H013
Quantity unit	Piece
Product designation	Integrated Voltage Detecting Systems VOIS+ C2m = 4 700 pF   System connector   without ground wire
Standard	IEC 61243-5, IEC 62271-213
Required data for order	Primary capacitance C1 of the coupling electrode Rated voltage UN

**Configuration**

Switching capacity C2m	4,700 pF
System connector (ankled)	✓
Earthing wire included	-

**Functionalities**

Voltage test	✓
--------------	---

**Dimensions**

Case height x width x depth	48 x 96 x 37 mm
Cutout height x width	45 x 92 mm
Norm cutout dimensions	DIN 43700
Installation type	Panel mounting

**Operating conditions**

Operating temperature	-25°C ... 55°C
Storage temperature	-30°C ... 80°C
Protection class	IP54
Voltage level	1..52 kV (Medium-voltage)
Rated frequency	50 Hz, 60 Hz
Type of interface	LRM

**Voltage supply**

Battery	No battery required
---------	---------------------

**Accessories**

Article number	Product designation
2500828_S999	Cable set   Custom-made for specific switchgear   On request   0,5 - 40 m