

The VOIS+ is an integrated Voltage Detecting Systems VDIS for checking for absence of voltage in medium voltage switchgear according to IEC 62271-213:2021 (or IEC 61243-5) with integrated three-phase continuous indication.



### Properties

#### Voltage Detecting Systems for Medium Voltage (VDIS)

Integrated three-phase Voltage Detecting Systems for medium voltage switchgear according to IEC 61243-5 and IEC 62271-213

#### No battery required

Voltage indication without battery or auxiliary voltage

#### Integrated three-phase measuring point

The device has a three-phase LR measuring point for phase comparison, rotating field direction measurement, etc.

#### Favorable alternative

to plug-in voltage indicators.

### Variants

Item number	Description
2502062	Integrated Voltage Detecting Systems VOIS+ with system connector
2502062_H001	Integrated Voltage Detecting Systems VOIS+ C2m = 680 pF   System connector   without ground wire
2502062_H002	Integrated Voltage Detecting Systems VOIS+ 2m = 1 000 pF   System connector   without ground wire
2502062_H003	Integrated Voltage Detecting Systems VOIS+ C2m = 2 200pF   System connector   without ground wire
2502062_H004	Integrated Voltage Detecting Systems VOIS+ C2m = 3 300 pF   System connector   without ground wire
2502062_H005	Integrated Voltage Detecting Systems VOIS+ 2m = 6 800 pF   System connector   without ground wire
2502062_H006	Integrated Voltage Detecting Systems VOIS+

Item number	Description
	C2m = 100 pF   System connector   without ground wire
2502062_H007	Integrated Voltage Detecting Systems VOIS+ C2m = 330 pF   System connector   without ground wire
2502062_H010	Integrated Voltage Detecting Systems VOIS+ C2m = 1 500 pF   System connector   without ground wire
2502062_H013	Integrated Voltage Detecting Systems VOIS+ C2m = 4 700 pF   System connector   without ground wire
2502062_H015	Integrated Voltage Detecting Systems VOIS+ 2m = 10 000 pF   System connector   without ground wire
2502062_H016	Integrated Voltage Detecting Systems VOIS+ C2m = 15 000 pF   System connector   without ground wire
2502062_H017	Integrated Voltage Detecting Systems VOIS+ C2m = 22 000 pF   System connector   without ground wire
2502062_H018	Integrated Voltage Detecting Systems VOIS+ C2m = 33 000 pF   System connector   without ground wire
2502062_H019	Integrated Voltage Detecting Systems VOIS+ C2m = 47 000pF   System connector   without ground wire
2502062_H020	Integrated Voltage Detecting Systems VOIS+ C2m = 68 000 pF   System connector   without ground wire
2502062_H021	Integrated Voltage Detecting Systems VOIS+ C2m = 150 000 pF   System connector   without ground wire
2502062_H022	Integrated Voltage Detecting Systems VOIS+ C2m = 470 pF   System connector   without ground wire
2502165_H001	Integrated Voltage Detecting Systems VOIS+ C2m = 680 pF   with earthing wire
2502165_H002	Integrated Voltage Detecting Systems VOIS+ C2m = 1000 pF   with earthing wire
2502165_H003	Integrated Voltage Detecting Systems VOIS+ C2m = 2200 pF   with earthing wire
2502165_H004	Integrated Voltage Detecting Systems VOIS+ C2m = 3.300 pF   with earthing wire
2502165_H005	Integrated Voltage Detecting Systems VOIS+ C2m = 6800 pF   with earthing wire
2502165_H006	Integrated Voltage Detecting Systems VOIS+ C2m = 100 pF   with earthing wire
2502165_H007	Integrated Voltage Detecting Systems VOIS+ C2m = 330 pF   with earthing wire
2502165_H008	Integrated Voltage Detecting Systems VOIS+ C2m = 1500 pF   with earthing wire
2502165_H009	Integrated Voltage Detecting Systems VOIS+ C2m = 4700 pF   with earthing wire
2502165_H010	Integrated Voltage Detecting Systems VOIS+ C2m = 10 000 pF   with earthing wire

Item number	Description
2502165_H011	Integrated Voltage Detecting Systems VOIS+ C2m = 5 000 pF   with earthing wire
2502165_H012	Integrated Voltage Detecting Systems VOIS+ C2m = 22 000 pF   with earthing wire
2502165_H013	Integrated Voltage Detecting Systems VOIS+ C2m = 33 000 pF   with earthing wire
2502165_H014	Integrated Voltage Detecting Systems VOIS+ C2m = 7 000 pF   with earthing wire
2502165_H015	Integrated Voltage Detecting Systems VOIS+ C2m = 68 000 pF   with earthing wire
2502165_H016	Integrated Voltage Detecting Systems VOIS+ C2m = 150 000 pF   with earthing wire
2502165_H017	Integrated Voltage Detecting Systems VOIS+ C2m = 470 pF   with earthing wire

## Technical Data

### Device data

Article number	2502165
Quantity unit	Piece
Product designation	Integrated Voltage Detecting Systems VOIS+
Standard	IEC 61243-5, IEC 62271-213
Required data for order	Primary capacitance C1 of the coupling electrode Rated voltage UN

### Configuration

Switching capacity C2m	Without C2m
System connector (ankled)	-
Earthing wire included	✓

### Functionalities

Voltage test	✓
--------------	---

### Dimensions

Case height x width x depth	48 x 96 x 37 mm
Cutout height x width	45 x 92 mm
Norm cutout dimensions	DIN 43700



### Dimensions

Installation type	Panel mounting
-------------------	----------------

### Operating conditions

Operating temperature	-25°C ... 55°C
Storage temperature	-30°C ... 80°C
Protection class	IP54
Voltage level	1..52 kV (Medium-voltage)
Rated frequency	50 Hz, 60 Hz
Type of interface	LRM

### Voltage supply

Battery	No battery required
---------	---------------------

## Accessories

Article number	Product designation
2500828_S999	Cable set   Custom-made for specific switchgear   On request   0,5 - 40 m